



Y Type (vertical kink)



P Type (straight lead)



Dimension Table

unit:mm

Diameter	5 φ	7 φ	10 φ	14 φ	20 φ
D max.	7.5	9.0	12.5	16.5	23
d±0.05	0.6	0.6	0.6/0.8	0.8/1.0	0.8/1.0
F±1.0	5.0	5.0	5.0/7.5	7.5/10.0	7.5/10.0
H max.	11.0	13	18	22	28
Hi max.	3.5	3.5	5	5	5
L ₁ min.	25.0	25.0	25.0	25.0	25.0
L min.	24.0	24.0	24.0	24.0	24.0

Table of T max., A & P₁ max.

unit:mm

Diameter	5 φ			7 φ			10 φ			14 φ			20 φ		
	T max.	A±0.8	P ₁ max.	T max.	A±0.8	P ₁ max.	T max.	A±0.8	P ₁ max.	T max.	A±0.8	P ₁ max.	T max.	A±0.8	P ₁ max.
180M	4.5	1.4	3.0	4.5	1.4	3.0	4.9	1.4	3.0	5.0	1.5	3.0	5.2	1.5	3.0
220L	4.5	1.5	3.0	4.5	1.5	3.0	4.9	1.5	3.0	5.0	1.6	3.0	5.3	1.6	3.0
270K	4.7	1.5	3.0	4.7	1.5	3.0	5.1	1.5	3.0	5.2	1.7	3.0	5.4	1.7	3.0
330K	4.7	1.6	3.0	4.7	1.6	3.0	5.1	1.6	3.0	5.2	1.8	3.0	5.4	1.8	3.0
390K	4.7	1.8	3.0	4.7	1.8	3.0	5.1	1.8	3.0	5.2	2.0	3.0	5.4	2.0	3.0
470K	5.0	1.8	3.0	5.0	1.8	3.0	5.5	1.8	3.0	5.6	2.0	3.0	5.6	2.0	3.0
560K	5.0	2.0	3.0	5.0	2.0	3.0	5.5	2.0	3.0	5.6	2.2	3.0	5.6	2.2	3.0
680K	5.5	2.3	3.0	5.5	2.3	3.0	6.0	2.3	3.0	6.1	2.5	3.0	6.1	2.5	3.0
820K	3.8	1.4	3.0	3.8	1.4	3.0	4.3	1.4	3.0	4.4	1.6	3.0	4.9	1.8	3.0
101K	3.9	1.4	3.0	3.9	1.4	3.0	4.4	1.4	3.0	4.5	1.6	3.0	5.1	1.8	3.0
121K	4.1	1.5	3.0	4.1	1.5	3.0	4.5	1.5	3.0	4.6	1.7	3.0	5.3	1.9	3.0
151K	4.5	1.8	3.0	4.5	1.8	3.0	4.9	1.8	3.0	5.1	2.0	3.0	5.6	2.2	3.0
181K	4.1	1.6	3.0	4.1	1.6	3.0	4.5	1.6	3.0	4.7	1.8	3.0	5.2	2.0	3.0
201K	4.2	1.6	3.0	4.2	1.6	3.0	4.6	1.6	3.0	4.8	1.8	3.0	5.3	2.0	3.0
221K	4.3	1.7	3.0	4.3	1.7	3.0	4.7	1.7	3.0	4.9	1.9	3.0	5.4	2.1	3.0
241K	4.4	1.7	3.0	4.4	1.9	3.0	4.8	1.9	3.0	5.0	2.1	3.0	5.5	2.3	3.0
271K	4.6	1.9	3.0	4.6	2.0	3.0	5.0	2.0	3.0	5.2	2.1	3.0	5.7	2.5	3.0
301K	4.8	1.9	3.0	4.8	2.1	3.0	5.2	2.2	3.0	5.4	2.3	3.0	5.9	2.7	3.0
331K	4.9	1.9	3.0	4.9	2.1	3.0	5.3	2.2	3.0	5.5	2.3	3.0	6.0	2.7	3.0
361K	5.1	2.4	3.0	5.1	2.5	3.0	5.5	2.5	3.0	5.7	2.7	3.0	6.2	2.9	3.0
391K	5.3	2.6	3.5	5.3	2.6	3.5	5.7	2.8	3.5	5.9	2.8	3.5	6.4	3.0	3.5
431K	6.1	2.7	3.5	6.1	2.9	3.5	6.5	3.1	3.5	6.7	3.1	3.5	7.2	3.3	3.5
471K	6.4	2.8	3.5	6.4	2.9	3.5	6.8	3.2	3.5	7.0	3.3	3.5	7.5	3.5	4.0
511K	6.6	3.1	4.0	6.6	3.1	4.0	7.0	3.7	4.0	7.2	3.7	4.0	7.7	3.9	4.0
561K	6.9	3.4	4.0	6.9	3.4	4.0	7.3	4.0	4.0	7.5	4.0	4.0	8.0	4.2	4.0
621K	7.2	3.7	4.0	7.2	3.7	4.0	7.6	4.6	4.0	7.8	4.4	4.0	8.3	4.7	4.0
681K	7.5	4.0	4.0	7.5	4.0	4.0	8.0	5.0	4.0	8.2	4.7	4.0	8.7	5.0	4.0
751K	7.9	4.3	4.0	7.9	4.3	4.0	8.4	5.0	4.0	8.6	4.9	4.0	9.1	5.1	4.0
781K				8.1	4.5	4.0	8.6	5.2	4.0	8.8	5.2	4.0	9.3	5.4	4.0
821K				8.3	4.7	4.0	8.8	5.2	4.0	9.0	5.2	4.0	9.5	5.4	4.0
911K							9.4	6.0	4.0	9.6	6.0	4.0	10.1	6.3	4.0
102K							9.9	6.0	4.0	10.1	6.2	4.0	10.7	6.4	4.0
112K							10.5	6.3	4.0	10.7	6.7	4.0	11.2	6.9	4.0
182K							12.6	9.8	6.0	12.8	10.2	6.0	13.5	10.4	6.0