


SPECIFICATION FOR APPROVAL

PRODUCT NAME: 59 1*4ports with transformer, W/O LED
and EMI, 10/100BT, Before 3.68

PRODUCT NO : KW-10002-1

CUSTOMER NO :

REV : _____ DATE : _____



ELECTRICAL SPECIFICATIONS:

1. 0 TURN RATIO: (P1-P2) : (J1-J2)
 (P7-P8) : (J3-J6)

: 1:1 ±3%
 : 1:1 ±3%

SIZE	DRAWING NO.	REV
A	KW-10002-1	01
SCALE	SHEET	
N/A	2 OF 7	

2.0 INDUCTANCE: (P1-P2) 350uH MIN @0.1V, 100KHZ, 8mA DC BIAS
(P7-P8) 350uH MIN @0.1V, 100KHZ, 8mA DC BIAS

3.0 LEAKAGE INDUCTANCE: P1-P2(WITH J1 AND J2 SHORT) : 0.3uH MAX @1MHZ
P7-P8(WITH J3 AND J6 SHORT) : 0.3uH MAX @1MHZ

4.0 INTERWINDING CAPACITANCE: (P1-P2): (J1-J2) : 35pF MAX @ 1MHZ
(P7-P8): (J3-J6) : 35pF MAX @ 1MHZ

5.0 DC RESISTANCE: (J1-J2): (J3-J6): 1.2 OHMS MAX

6.0 RETURN LOSS: 1MHZ TO 30MHZ : -18dB MIN
30MHZ TO 80MHZ : -12dB MIN

7.0 DIELECTRIC WITHSTAND: (P1-P2): (J1-J2) : 1500VAC
(P7-P8): (J3-J6) : 1500VAC

8.0 INSERTION LOSS: RS=RL=100OHM 100KHZ TO 80MHZ : -1.1dB MIN



9.0 RISE TIME : RS=100OHMSAND RL=100OHMS : 3.0nS MAX
OUTPUT VOLTAGE=1V PEAK : 3.0nS MAX
PULSE WIDTH=112NS

10.0 CROSS TALK: 1MHZ TO 100MHZ 40dB TYP

11.0 COMMON TO COMMON MODE ATTENUATION: 30MHZ TO 100MHZ : 35dB TYP


SIZE	DRAWING NO.	REV
A	KW-10002-1	01
SCALE		SHEET
N/A		3 OF 7

MECHANIC SPECIFICATIONS:




NOTES:

1. CONNECTOR MATERIAL:
HOUSING: THERMOPLASTIC UL94 V-0
CONTACT/SHIELD: COPPER ALLOY
SHIELD PLATING: NICKEL OR TIN
CONTACT PLATING: SELECTIVE GOLD,
- 50 MICRO-INCHS MIN
- 30 MICRO-INCHS MIN
- 15 MICRO-INCHS MIN
- 6 MICRO-INCHS MIN
- 3 MICRO-INCHS MIN
- IN CONTACT AREA
2. PIN NOT ELECTRICALLY CONNECTED MAYBE OMITTED SEE ELECTRICAL DRAWING FOR OMITTED PINS
3. TOLERANCES COMPLY WITH F. C. C DIMENSION REQUIREMENTS
4. WAVE SOLDER COMPATIBLE-PREHEAT 125 C DEGREE/90SECS
5. ALL TOLERANCES NOT OTHERWISE SPECIFIED TO BE ±0.1mm.



SIZE	DRAWING NO.	REV
A	KW-10002-1	01
SCALE		SHEET
N/A		4 OF 7


MECHANIC SPECIFICATIONS:



P. C. B RECOMMENDED HOLE LAYOUT SEEN FROM COMPONENT SIDE.


ALL CENTERLINE DIMENSIONS ARE BASIC

SIZE	DRAWING NO.	REV
A	KW-10002-1	01
SCALE		SHEET
N/A		5 OF 7



.015" (0.38) FROM TOP OF PCB TO BOTTOM OF OPENING.

1 SUGGESTED PANEL OPENING (N. T. S)



1. THE SUGGESTED PANEL OPENING IS INTENDED TO GIVE THE USER THE ABILITY TO HAVE REASONABLE JACK/PANEL CLEARANCES CAPABILITY.
2. ALL TOLERANCES NOT OTHERWISE SPECIFIED TO BE ± 0.005 INCH (0.13)

SIZE	DRAWING NO.	REV
A	KW-10002-1	01
SCALE		SHEET
N/A		2 OF 7